



D-RING IS INSTALLED INTO THE TWO HOLES NEAREST THE BEND ON THE MOUNTING BRACKETS IN EITHER THE 19" OR 23" CONFIGURATION. THE SCREW INSTALLS FROM THE BACK SIDE OF THE BRACKET INTO THE PEM NUT IN THE D-RING.

REV	DESCRIPTION	DRWN	CHK	DATE
001	ECN-000021 REPLACED TAPPED HOLE WITH PEM.	SMJ	SMJ	12/21/10
000		SMJ	SMJ	06/20/05

		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO ENGINUITY COMMUNICATIONS CORP. AND SHALL NOT BE USED WITHOUT WRITTEN PERMISSION.	
UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: FRACTION: +/- 1/16" DECIMAL: .X = +/- .050 .XX = +/- .020 .XXX = +/- .005 ANGLES: +/- 5 degrees		TITLE: INSTALLATION CARD, DRNG-1	
		PART NUMBER: 001-04-000002	REV. 001
		SCALE: 1:1	CAD FILE: 001-04-000002rev001.cdr SHT. 1 OF 1