

Fiber Drop Cable - SC/APC To Blunt

Factory-terminated outdoor fiber drop cable assembly



Engenuity Fiber Drop Cable assembly features an SC/APC connector on one end and a raw/blunt on the other end for FTTx applications. Constructed with an outdoor rated flat drop cable, the cable assembly withstands the harsh outdoor environment. Ideal for direct buried and conduit duct applications.

FEATURES

- Dielectric flat drop cable with toneable copper element
- SC/APC connector with 8" long 3mm transition on one end, raw on the opposite end
- Available with other connector and cable type configurations
- Outdoor drop cable ideal for direct buried and conduit applications



SC/APC Connector to Blunt

STANDARDS

- Termination tested to Telcordia GR-326
- BABA compliant options available

SPECIFICATIONS

- Flat oval, single mode, G.657.A1, black jacket drop cable
- Insertion Loss, Typical per connector: 0.20dB, 0.50 dB maximum
- Reflection: ≤ -65 dB

CABLES



Fiber Drop Cable - SC/APC To Blunt



Packaged

ORDERING INFORMATION

SC/APC to stub, toneable flat drop, G.657.A1,
8" 3mm breakout

Enginuity Part #	Length
FD-051-350XXM	350
FD-051-500XXM	500
FD-051-650XXM	650
FD-051-750XXM	750
FD-051-1000XXM	1,000
FD-051-1200XXM	1,200
FD-051-1500XXM	1,500
FD-051-1750XXM	1,750